



Safety data sheet according to UK REACH

Printing date 30.10.2025

Version number 1

Revision: 30.10.2025

*

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**

- **Trade name:** UltraSeal XT™ Hydro™

- **Article number:**

SDS 239-001.11R01, 71109, 71110, 71111, 56315, 87511, 3533, 3535, 3536-1, REF3536-1, S3529, 14852, 87510, 3532, 3534, 3536, REF3536

- **Relevant identified uses of the substance or mixture and uses advised against**

Professional Dental Pit and Fissure Sealant

- **Application of the substance / the mixture** Professional Dental Pit and Fissure Sealant

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Ultradent Products Inc.
505 W. Ultradent Drive (10200 S)
South Jordan, UT 84095-3942
USA
onlineordersupport@ultradent.com
(800) 552-5512

EC Responsible Person
Ultradent Products GmbH
Am Westhover Berg 30
51149 Cologne Germany
Email: infoDE@ultradent.com
Office Phone: +49(0)2203-35-92-0

- **Further information obtainable from:** Customer Service

- **Emergency telephone number:**

CHEMTREC (NORTH AMERICA) : +1 (800) 424-9300
(INTERNATIONAL) : +(703) 527-3887

2 Hazards identification

- **Classification of the substance or mixture**

- **Classification according to Regulation (EC) No 1272/2008**



Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- **Labelling according to Regulation (EC) No 1272/2008** Void

- **Hazard pictograms** GHS07

- **Signal word** Warning

- **Hazard-determining components of labelling:**

Triethylene Glycol Dimethacrylate
Methacrylic Acid
Diurethane Dimethacrylate
Organophosphine Oxide

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 30.10.2025

Version number 1

Revision: 30.10.2025

Trade name: UltraSeal XT™ Hydro™

(Contd. of page 1)

· Hazard statements

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

· Mixtures**· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

CAS: 109-16-0 EINECS: 203-652-6	Triethylene Glycol Dimethacrylate ⚠ Skin Sens. 1, H317	>10-<30%
CAS: 72869-86-4 EINECS: 276-957-5	Diurethane Dimethacrylate ⚠ Skin Sens. 1, H317; Aquatic Chronic 3, H412	>5-<20%
CAS: 1830-78-0 EINECS: 217-388-4	Glycerol Dimethacrylate ⚠ Skin Irrit. 2, H315; STOT SE 3, H335	≥5-<10%
	Trimethylolpropane Trimethacrylate ⚠ Aquatic Chronic 2, H411	≥0.25-<2.5%
	Trade Secret ⚠ Skin Corr. 1A, H314	≥1-<5%
CAS: 79-41-4 EINECS: 201-204-4	Methacrylic Acid ⚠ Acute Tox. 3, H311; ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 1 %	≤1%
CAS: 10287-53-3 EINECS: 233-634-3	Ethyl-4-Dimethylamino Benzoate ⚠ Repr. 1B, H360; ⚠ Aquatic Chronic 2, H411	≥0.1-<1%
	Organophosphine Oxide ⚠ Skin Sens. 1A, H317; Aquatic Chronic 4, H413	<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· Description of first aid measures**· General information:** Immediately remove any clothing soiled by the product.**· After inhalation:**

Seek medical treatment in case of complaints.

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.**· After eye contact:** Rinse opened eye for several minutes under running water.**· After swallowing:** If symptoms persist consult doctor.

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 30.10.2025

Version number 1

Revision: 30.10.2025

Trade name: UltraSeal XT™ Hydro™

(Contd. of page 2)

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters:**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
See product labelling.
Keep container tightly sealed.
- **Specific end use(s)** Professional Dental Pit and Fissure Sealant

8 Exposure controls/personal protection

- **Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

79-41-4 Methacrylic Acid

WEL	Short-term value: 143 mg/m ³ , 40 ppm
	Long-term value: 72 mg/m ³ , 20 ppm

- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 30.10.2025

Version number 1

Revision: 30.10.2025

Trade name: UltraSeal XT™ Hydro™

(Contd. of page 3)

- **Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Hand protection**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye/face protection** Goggles recommended during refilling
- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Fluid
- **Colour:** According to product specification
- **Odour:** Acrylic
- **Odour threshold:** Not determined.
- **Melting point/freezing point:** Undetermined.
- **Boiling point or initial boiling point and boiling range** Undetermined.
- **Flammability** Not applicable.
- **Lower and upper explosion limit**
- **Lower:** Not determined.
- **Upper:** Not determined.
- **Flash point:** Not applicable.
- **Decomposition temperature:** Not determined.
- **pH** Not applicable (non-aqueous)
- **Viscosity:**
- **Kinematic viscosity** Not determined.
- **Dynamic:** Not determined.
- **Solubility**
- **water:** Not miscible or difficult to mix.

(Contd. on page 5)

GB

Safety data sheet according to UK REACH

Printing date 30.10.2025

Version number 1

Revision: 30.10.2025

Trade name: UltraSeal XT™ Hydro™

(Contd. of page 4)

· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.67 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Other information	
· Appearance:	
· Form:	Liquid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Change in condition	
· Evaporation rate	Not determined.
· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions:** No dangerous reactions known.
- **Conditions to avoid:** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 30.10.2025

Version number 1

Revision: 30.10.2025

Trade name: UltraSeal XT™ Hydro™

(Contd. of page 5)

· **LD/LC50 values relevant for classification:****ATE (Acute Toxicity Estimates)**

Oral	LD50	102,743-109,873 mg/kg (rat)
Dermal	LD50	48,464-51,827 mg/kg
Inhalative	LC50/4 h	688-736 mg/l (rat)

109-16-0 Triethylene Glycol Dimethacrylate

Oral	LD50	>5,000 mg/kg (rat)
	LC50 Fish	16.4 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (mouse)

72869-86-4 Diurethane Dimethacrylate

Oral	LD50	>5,000 mg/kg (rat)
------	------	--------------------

79-41-4 Methacrylic Acid

Oral	LD50	1,250 mg/kg (mouse)
		1,060 mg/kg (rat)
		1,200 mg/kg (rabbit)
	LC50 Fish	86 mg/l (Fish)
Dermal	LD50	1,000 mg/kg (guinea pig)
		500 mg/kg (rabbit)
Inhalative	LC50/4 h	7.1 mg/l (rat)

Organophosphine Oxide

Oral	LD50	>2,000 mg/kg (rat)
	LC50 Fish	>0.09 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (rat)

· **Respiratory or skin sensitisation** May cause an allergic skin reaction.· **STOT-single exposure** May cause respiratory irritation.· **Information on other hazards**· **Endocrine disrupting properties**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**· **Aquatic toxicity:****109-16-0 Triethylene Glycol Dimethacrylate**

EC50	>100 mg/kg (Algae)
Biodegradability	28 days (Aerobic) (Biodegradability testing)
Aqua toxicity	32 mg/l (daphnia) (No Observed Effect Concentration)

72869-86-4 Diurethane Dimethacrylate

EC50	>0.6 mg/kg (Algae)
Biodegradability	28 days (Aerobic) (Biodegradability testing)

79-41-4 Methacrylic Acid

EC50	17,000 mg/kg (Algae)
	<180 mg/kg (daphnia) (Toxicity to aquatic invertebrates)

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 30.10.2025

Version number 1

Revision: 30.10.2025

Trade name: UltraSeal XT™ Hydro™

(Contd. of page 6)

Organophosphine Oxide

EC50 (static)	>1.175 mg/kg (daphnia) (Toxicity to aquatic invertebrates)
Aqua toxicity	≥0.008 mg/l (daphnia) (Daphnia Magna Reproduction Test)
Toxicity to Aquatic Plants (static)	>0.26 mg/l (Plant) (Toxicity to algae)

- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Dispose of contents/container in accordance with international, federal, state, and local regulations.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|--|-----------------|
| · UN number or ID number | |
| · ADR, ADN, IMDG, IATA | not regulated |
| · UN proper shipping name | |
| · ADR, ADN, IMDG, IATA | not regulated |
| · Transport hazard class(es) | |
| · ADR, ADN, IMDG, IATA | |
| · Class | not regulated |
| · Packing group | |
| · ADR, IMDG, IATA | not regulated |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Not Applicable |
| · Maritime transport in bulk according to IMO instruments | Not applicable. |
| · UN "Model Regulation": | not regulated |

GB

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 30.10.2025

Version number 1

Revision: 30.10.2025

Trade name: UltraSeal XT™ Hydro™

(Contd. of page 7)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

· **Regulated poisons**

None of the ingredients is listed.

· **Reportable explosives precursors**

None of the ingredients is listed.

· **Reportable poisons**

None of the ingredients is listed.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Chemical safety assessment:**

Device is biocompatible when used as directed by dental professionals per ISO 10993-1

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases from Section 3**

H302 Harmful if swallowed.

H311 Toxic in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H360 May damage fertility or the unborn child.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

· **Department issuing SDS:** Environmental, Health, and Safety

· **Contact:** Customer Service

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

(Contd. on page 9)

Safety data sheet
according to UK REACH

Printing date 30.10.2025

Version number 1

Revision: 30.10.2025

Trade name: UltraSeal XT™ Hydro™

(Contd. of page 8)

*ATE: Acute toxicity estimate values**Acute Tox. 4: Acute toxicity – Category 4**Acute Tox. 3: Acute toxicity – Category 3**Skin Corr. 1A: Skin corrosion/irritation – Category 1A**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Skin Sens. 1: Skin sensitisation – Category 1**Skin Sens. 1A: Skin sensitisation – Category 1A**Repr. 1B: Reproductive toxicity – Category 1B**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3**Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4***. * Data compared to the previous version altered.**

GB