

Printing date 10.10.2025 Version number 1 Revision: 10.10.2025

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: OpalescenceTM Boost PF 35% HP Mixed
- · Article number: SDS 468-001.02R01, 1005860, 1009827, 13470, 4488, 6242
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Professional tooth bleaching gel in-office.
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Ultradent Products Inc.

505 W. Ultradent Drive (10200 S)

South Jordan, UT 84095-3942

USA

on line order support@ultradent.com

(800) 552-5512

EC Responsible Person Ultradent Products GmbH

Am Westhover Berg 30

51149 Cologne Germany

Email: infoDE@ultradent.com

Office Phone: +49(0)2203-35-92-0

- · Further information obtainable from: Customer Service
- · Emergency telephone number:

CHEMTREC (NORTH AMERICA): +1 (800) 424-9300

(INTERNATIONAL): +(703) 527-3887

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



flame over circle

Ox. Liq. 2 H272 May intensify fire; oxidiser.



corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Printing date 10.10.2025 Version number 1 Revision: 10.10.2025

Trade name: OpalescenceTM Boost PF 35% HP Mixed

(Contd. of page 1)

· Hazard pictograms GHS03, GHS05

· Signal word Danger

· Hazard-determining components of labelling:

Hydrogen Peroxide

· Hazard statements

H272 May intensify fire; oxidiser.

H315 Causes skin irritation.

H318 Causes serious eye damage.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

· Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 56-81-5	Glycerin	<40%
EINECS: 200-289-3	substance with a Community workplace exposure limit	
CAS: 7722-84-1	Hydrogen Peroxide	>10-≤25%
EINECS: 231-765-0	♦ Ox. Liq. 1, H271; ♦ Skin Corr. 1A, H314; ♦ Acute Tox. 4, H302; Acute Tox. 4, H332	
	Specific concentration limits: Ox. Liq. 1; H271: $C \ge 70 \%$	
	Ox. Liq. 2; H272: $50 \% \le C < 70 \%$	
	Skin Corr. 1A; H314: C ≥ 70 %	
	Skin Corr. 1B; H314: 50 % ≤ C < 70 %	
	Skin Irrit. 2; H315: 35 % ≤ C < 50 %	
	Eye Dam. 1; H318: C ≥ 8 %	
	Eye Irrit. 2; H319: 5 % ≤ C < 8 %	
	STOT SE 3; H335: C ≥ 35 %	
	Synthetic Amorphous, Pyrogenic Silica	1-10%
	substance with a Community workplace exposure limit	
CAS: 1310-58-3	Potassium Hydroxide	≥0.5-<2%
EINECS: 215-181-3	♦ Skin Corr. 1A, H314; ♦ Acute Tox. 4, H302	
	Specific concentration limits: Skin Corr. 1A; H314: C≥5 %	
	Skin Corr. 1B; H314: 2 % ≤ C < 5 %	
	Skin Irrit. 2; H315: 0.5 % ≤ C < 2 %	
	Eye Irrit. 2; H319: 0.5 % ≤ C < 2 %	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

Printing date 10.10.2025 Version number 1 Revision: 10.10.2025

Trade name: OpalescenceTM Boost PF 35% HP Mixed

(Contd. of page 2)

4 First aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Firefighting measures

- Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters:
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Precautions for safe handling: No special precautions are necessary if used correctly.
- · Information about fire and explosion protection: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

GB

Printing date 10.10.2025 Version number 1 Revision: 10.10.2025

Trade name: OpalescenceTM Boost PF 35% HP Mixed

(Contd. of page 3)

8 Exposure controls/personal protection

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

56-81-5 Glycerin

WEL Long-term value: 10 mg/m³

7722-84-1 Hydrogen Peroxide

WEL Short-term value: 2.8 mg/m³, 2 ppm Long-term value: 1.4 mg/m³, 1 ppm

Synthetic Amorphous, Pyrogenic Silica

TWA Short-term value: 6 mg/m³

1310-58-3 Potassium Hydroxide

WEL Short-term value: 2 mg/m³

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not required.
- · Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact breakthrough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· **Body protection:** Protective work clothing

Printing date 10.10.2025 Version number 1 Revision: 10.10.2025

Trade name: OpalescenceTM Boost PF 35% HP Mixed

(Contd. of page 4)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odorless

Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.
 Boiling point or initial boiling point and boiling range Undetermined.
 Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: Not applicable.
Decomposition temperature: Not determined.

· pH at 20 °C 6.5-8.5

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

·Solubility

• water: Partly soluble.
• Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C: 23.3 hPa (7732-18-5 Water)

· Density and/or relative density

Density at 20 °C:
 Relative density
 Bulk density:
 Vapour density
 Not determined.
 Not determined.
 Not determined.

· Other information

· Appearance:

· Form: Gel

· Important information on protection of health and environment, and on safety.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Change in condition

• Evaporation rate Not determined.

Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void Void · Aerosols · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void

· Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases

in contact with water Void

• Oxidising liquids May intensify fire; oxidiser.

(Contd. on page 6)

Printing date 10.10.2025 Version number 1 Revision: 10.10.2025

Trade name: OpalescenceTM Boost PF 35% HP Mixed

(Contd. of page 5)

· Oxidising solids	Void	
· Organic peroxides	Void	
· Corrosive to metals	Void	
· Desensitised explosives	Void	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions: No dangerous reactions known.
- · Conditions to avoid: No further relevant information available.
- · Incompatible materials:

Alkalis

Heavy Metals

Combustible Materials

Reducing Agents

Organic materials

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	values relevant for class	ification:
ATE (Acı	ıte Toxicity Estimates)	
Oral	LD50	2,041 mg/kg
Inhalative	LC50/4 h	44.9 mg/l
56-81-5 C	Glycerin	
Oral	LD50	7,750 mg/kg (guinea pig)
		4,100 mg/kg (mouse)
		5,570 mg/kg (rat)
		27,000 mg/kg (rabbit)
	LC50 Fish	>5,000 mg/l (Fish)
Dermal	LD50	>21,900 mg/kg (rat)
		10,000 mg/kg (rabbit)
7722-84-	l Hydrogen Peroxide	
Oral	LC50 Fish	16.4 mg/l (Fish)
Synthetic	Amorphous, Pyrogenic S	Silica
Oral	LD50	>5,000 mg/kg (rat) (Oral Test Method)
	LC50 Fish	>10,000 mg/l (Fish) (Toxicity to fish)
Dermal	LD50	>2,000 mg/kg (rabbit) (Dermal test method)
	LC50(Daphnia magna)	>1,000-10,000 mg/l (daphnia) (Toxicity to aquatic invertebrates)
1310-58-	3 Potassium Hydroxide	
Oral	LD50	214 mg/kg (rat)

- C

(Contd. of page 6)

Safety data sheet according to UK REACH

Printing date 10.10.2025 Version number 1 Revision: 10.10.2025

Trade name: OpalescenceTM Boost PF 35% HP Mixed

LC50 Fish 80 mg/l (Fish)

Primary irritant effect:

- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity:

56-81-5 Glycerin

EC50 >10,000 mg/kg (Bacteria)

7722-84-1 Hydrogen Peroxide

EC50 1.38 mg/l (Algae)

2.4 mg/l (daphnia)

- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties.
- · Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Dispose of contents/container in accordance with international, federal, state, and local regulations.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

- · UN number or ID number
- · ADR, IMDG, IATA UN2014
- · UN proper shipping name
- · **ADR** 2014 HYDROGEN PEROXIDE, AQUEOUS SOLUTION

(Contd. on page 8)

Printing date 10.10.2025 Version number 1 Revision: 10.10.2025

Trade name: OpalescenceTM Boost PF 35% HP Mixed

	(Contd. of pa
IMDG, IATA	HYDROGEN PEROXIDE, AQUEOUS SOLUTION
Transport hazard class(es)	
ADR	
551	
Class Label	5.1 Oxidising substances. 5.1+8
IMDG	
51	
Class Label	5.1 Oxidising substances. 5.1/8
IATA	3.170
Class Label	5.1 Oxidising substances. Forbidden
Packing group ADR, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler code): EMS Number:	Warning: Oxidising substances. ; 58 F-H,S-Q
Segregation groups	(SGG16) Peroxides
Stowage Category	D
Stowage Code	SW1 Protected from sources of heat.
Segregation Code	SG16 Stow "separated from" class 4.1 SG59 Stow "separated from" SGG14-permanganates SG72 See 7.2.6.3.2.
Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
Tugues out agtagous	Maximum net quantity per outer packaging: 500 ml
Transport category Tunnel restriction code	2 E

(Contd. on page 9)

Printing date 10.10.2025 Version number 1 Revision: 10.10.2025

Trade name: OpalescenceTM Boost PF 35% HP Mixed

(Contd. of page 8)

	(Conta. of page o)
· IMDG	1.7
· Limited quantities (LQ) · Excepted quantities (EQ)	IL Code: E2
Excepteu quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2014 HYDROGEN PEROXIDE, AQUEOUS SOLUTION, 5.1 (8), II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Poisons Act

· Regulated explosives precursors

7722-84-1 Hydrogen Peroxide

12%

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

7757-79-1 Potassium Nitrate

Listed

· Reportable poisons

-	*	
1310-58-3	Potassium Hydroxide	17% of total caustic alkalinity
7681-49-4	Sodium Fluoride	Listed

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P8 OXIDISING LIQUIDS AND SOLIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 50 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- · Chemical safety assessment: A chemical safety assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases from Section 3

H271 May cause fire or explosion; strong oxidiser.

H272 May intensify fire; oxidiser.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

- · Department issuing SDS: Environmental, Health, and Safety
- · Contact: Customer Service

(Contd. on page 10)

Printing date 10.10.2025 Version number 1 Revision: 10.10.2025

Trade name: OpalescenceTM Boost PF 35% HP Mixed

(Contd. of page 9)

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

ATE: Acute toxicity estimate values

Ox. Liq. 1: Oxidizing liquids – Category 1

Ox. Liq. 2: Oxidizing liquids - Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

* Data compared to the previous version altered.

CD.